

**SNC-CH220**

E Series fixed Full HD (1080p) resolution network security camera

The SNC-CH220 is an indoor high definition (1080p, supporting H.264 at 30fps) 3 Megapixel (1920x 1440 maximum resolution) fixed camera with Optical Day/Night function, DEPA and ONVIF compliance. It supports dual streaming and triple codec encoding.

Sony's Exmor CMOS sensor provides excellent pictures and event detection for effective evidence gathering.

Sony's E-Series cameras have outstanding picture quality and a range of features at an affordable price.

1-year PrimeSupport is included as standard within the EU, Norway and Switzerland. This gives users access to an expert helpdesk and, in the unlikely event of a failure, will arrange for an advance replacement unit to be delivered within a target time of one working day. An additional 2-years support is also available as an option.

## Features

### DEPA

The SNC-CH220 offers intelligent video analytics, based on the Sony DEPA platform. DEPA is a combined function of the intelligence built in to the camera and rules/filters that determine which images should be recorded or when an alarm should be triggered.

### EXMOR® and CMOS Sensor®

High resolution CMOS sensor® with low noise characteristics for improved image acquisition. Derived from Sony's broadcast product range, EXMOR® is one of the highest quality image sensors available.

### Power over Ethernet (PoE) capability

Supporting Power over Ethernet (PoE), the camera can be powered using the same Ethernet cable it uses for data transfer. This feature greatly reduces the physical infrastructure costs and speed of deployment.

### ONVIF (Open Network Video Interface Forum) compliance

The ONVIF (Open Network Video Interface Forum) defines a common protocol for the exchange of information between network video devices including automatic device discovery and video streaming. Allows interoperability between network video devices.

### Full HD (1920x1080p) resolution

Detailed Full HD progressive images. Progressive acquisition (as opposed to interlace) means that images are more stable to view, contain more information and compress more efficiently - without "interlace artifacts".

### Supports multiple industry standard codecs: H264, MPEG-4 and JPEG with dual streaming capability

This multi-codec camera supports three compression formats: JPEG, the best choice of high-quality still images; MPEG-4, the format that provides clear moving images efficiently over limited-bandwidth networks; and H.264, the alternative for severely limited-bandwidth networks, providing twice the efficiency of MPEG-4. The camera can generate multiple streams simultaneously.

### Optical Day/Night

Optimises sensitivity in day and night conditions. As night falls, an infra-red filter is automatically removed and the camera switches to monochrome. In this mode, the camera can acquire images extremely low light conditions.

### Stream Squared Function

An incredibly useful function that allows simultaneous streaming of two 4:3 aspect ratio videos in user-selectable SD resolutions. You can select the entire image or a portion of the image from the original view and resize to SD resolution. With this feature the SNC-CH220 can replace two SD cameras installed in the same line of view.

### Easy Focus

Easy Focus simplifies installation by making it easy to set up the focus settings of the camera.

## Analogue Monitor Output

This allows an analogue video monitor to be connected directly to the camera.

## Technical Specifications

Camera	
Image device	1/2.8 type progressive scan "Exmor" CMOS sensor
Minimum illumination	0.70lx (Color), 0.45lx (BW) (F1.2/ AGC 42dB/ 50IRE [IP])
Number of effective pixels (H x V)	Approx. 3.27Megapixel (2096x1561)
Electronic shutter speed	1 s to 1/10000 s
Gain control	Auto
Exposure control	Auto, EV Compensation, Auto Slow Shutter
White balance mode	Auto (ATW, ATW-PRO), Preset, One-push WB, Manual
Lens type	CS Mount Vari-focal lens
Zoom ratio	Optical 2.1X
Horizontal viewing angle	101.2 degrees to 47.0 degrees
Focal length	f=2.8 mm to 6.0 mm
F-number	F1.3 (Wide), F1.9 (Tele)
Minimum objects distance	300 mm
Powered focus	Yes (Easy Focus)

Camera Features	
Day/Night *1	Yes
Noise reduction	Yes

Image	
Codec image size (H x V)	1920 x 1440, 1600 x 1200, 1680 x 1056, 1920 x 1080, 1440 x 912, 1376 x 768, 1280 x 960, 1280 x 800, 1280 x 720, 1280 x 1024, 1024 x 768, 1024 x 576, 800 x 480, 768 x 576, 720 x 576, 704 x 576, 720 x 480, 640 x 480, 640x 368, 384 x 288, 320 x 240, 320 x 192 (H.264, MPEG-4, JPEG)
Video compression format	H.264, MPEG-4, JPEG
Codec streaming capability	Dual streaming
Maximum frame rate	H264: 20fps (1920 x 1440) / 30fps (1920 x 1080) MPEG-4: 15fps (1920 x 1440) / 20 fps (1920 x 1080) JPEG: 10fps (1920 x 1440) / 15fps (1920 x 1080)

Scene Analytics	
Intelligent motion detection	Yes

Network	
Protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, FTP (client only), SMTP, DHCP, DNS, NTP, RTP/RTCP, RTSP, SNMP (MIB-2)
ONVIF conformance	Yes
Number of clients	5
Authentication	IEEE802.1X

Analog Video Output	
Signal system	NTSC / PAL

Interface	
Ethernet	10BASE-T / 100BASE-TX (RJ-45)
Analog monitor output	Phono jack x 1 (1.0 Vp-p, 75 ohms, unbalanced, sync negative)
Sensor input	x 1, make contact, break contact
Alarm output	x 1, 24V AC/DC, 1A (mechanical relay outputs electrically isolated from the camera)

General	
Mass	550 g (1 lb 3 oz) with lens
Dimensions	72 x 63 x 197.3 mm (2 7/8 x 2 1/2 x 7 3/4 inches)
Power requirements	PoE (IEEE802.3af compliant)
Power consumption	5.0 W Max.
Starting temperature	0 °C to 50 °C (32 °F to 122°F)
Working temperature	-10 °C to +50 °C (14 °F to 122 °F)
Storage temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Safety regulation	UL2044, FCC 15B Class A, IC Class A, IEC60950-1, EN55022(A)+EN55024+EN50130-4, VCCI Class A, C-Tick Class A

**System Requirements**

Operating system	Microsoft Windows XP, Windows Vista(32bit), Windows 7(32bit)
Processor	Intel Core2 Duo 2 GHz or higher
Memory	1 GB or more
Web browser	Microsoft Internet Explorer Ver. 6.0, Ver. 7.0, Ver. 8.0 Firefox Ver.3.5 (Plug-in free viewer only) Safari Ver.4.0 (Plug-in free viewer only) Google Chrome Ver.4.0 (Plug-in free viewer only)

**Supplied Accessories**

Supplied Accessories	CD-ROM (User's guides, and Supplied programs), Wire rope, Screw M4, Installation Manual
----------------------	---

**Notes**

Notes	*1 Removable IR Cut Filter. * The SNC-CH220 includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit ( <a href="http://www.openssl.org/">http://www.openssl.org/</a> ).
-------	---