

ENGLISH

## PUNTO Side-opening housing



*be Safe and Save.*



**HEADQUARTERS ITALY VIDEOTEC S.p.A.**  
Via Friuli, 6 - I-36015 Schio (VI) Italy  
Tel. +39 0445 697411 - Fax +39 0445 697414  
Email: info@videotec.com

**UK/IRELAND SALES REPRESENTATIVE**  
Tel./Fax +44 01353 775438 (Sales)  
Tel. +44 0113 815 0047 (Technical support)  
Tel. +44 0113 815 0031 (Orders/Shipping dept.)  
Email: uksales@videotec.com

**ASIA PACIFIC VIDEOTEC (HK) Ltd**  
Unit C 24 Floor - Gold King Industrial Building  
35-41, Tai Lin Pai Road - Kwai Chung, NT, Hong Kong  
Tel. +852 2333 0601 - Fax +852 2311 0026  
Email: info@videotec.com.hk

**FRANCE VIDEOTEC FRANCE S.à.r.l.**  
Voie du Futur - Zac des Portes - 27100 Val de Reuil, France  
Tel. +33 2 32094900 - Fax +33 2 32094901  
Email: info@videotec-france.com

**AMERICAS VIDEOTEC SECURITY, Inc.**  
The Lower level South Suite - The Ottilio Office Complex I  
555 Preakness Ave. - Totowa, NJ 07512 - U.S.A.  
Tel. +1 973 5950788 - Fax +1 425 6484289  
Email: usasales@videotec.com - www.videotec.us

[www.videotec.com](http://www.videotec.com)

# PUNTO THE NEW HOUSING, COST-EFFECTIVE, NO COMPROMISE



PUNTO is the new camera housing resulting out of over 25 years' experience in the field of design and manufacture of video-security products.

## KEY BENEFITS

### COMPETITIVE

The aim of the new PUNTO housing is to respond to market requirement for **highly competitive** solutions that do not compromise on quality and reliability, distinctive of all Videotec's products.

### STYLISH

The aerodynamic and streamlined shape of the new PUNTO housing is striking. The design is studied to optimize both internal and external spaces. The housing dimensions are suitable to **accommodate various cameras and lenses** without any compromise on quality and user's friendliness.

### STRONG CONSTRUCTION

The accurate construction and the fine selection of the raw materials provide a **high level of protection** against weather conditions. Made of a techno-polymer, the new housing features the **side opening for ease of access** to the camera and the lens.

### FLEXIBILITY

The front of PUNTO housings is designed to provide good protection from sun rays and rain and allows a **wide angle of view to the camera**.

The camera power supply is available as an option.

This new housing works out perfectly in **various mounting** configurations with or without cable management for any installation requirement both indoors and outdoors.



## AVAILABLE VERSIONS



## TECHNICAL DATA

### GENERAL

Entirely constructed from technopolymer

RAL9002 Colour

Stainless steel external screws

Supplied with instruction manual, desiccant bag, accessories for camera and lens mounting

### MECHANICAL

2xM16 cable glands

Glass window (WxH): 60/95x63mm (2.4/3.7x2.5in)

Internal usable area (WxH): 70x70mm (2.7x2.7in)

Internal usable length with and without accessories: 250mm (9.8in)

### ELECTRICAL

Heater Ton 15°C±3°C (59°F ±5°F) Toff 22°C±3°C (71.6°F ±5°F)

IN 12Vdc, 1.6A max

IN 24Vac, 50/60Hz 1.5A max

IN 115Vac, 50/60Hz 0.5A max

IN 230Vac, 50/60Hz 0.25A max

### AVAILABLE VERSIONS

HOT39D1A000 Housing with heater 115/230Vac

HOT39D1A085 Housing with heater 115/230Vac and wall bracket WBOV2A

HOT39D2A000 Housing with heater 12Vdc/24Vac

HOT39D2A085 Housing with heater 12Vdc/24Vac and wall bracket WBOV2A

### ACCESSORIES

OHOTS Sunshield

OHOTPS1 Wide range camera power supply IN 100-240Vac - OUT 12Vdc, 1A

OHOTPS2 Camera power supply IN 230Vac - OUT 24Vac, 400mA

### BRACKETS AND ADAPTORS

WBJA Wall bracket with ball joint

WBOVA2 Wall bracket with internal cable channel

### ENVIRONMENT

Indoor / Outdoor

Operating temperature with heater: -20°C / +60°C (-4°F / +140°F)

Very good resistance to the following chemical agents: basics, alcohols, gasses, hydrocarbon

Good resistance: organic and inorganic acids, oils

Low resistance: solvents

### CERTIFICATIONS

CE EN61000-6-3, EN60950-1, EN50130-4

IP66/IP67 EN60529